

MATERIAL SAFETY DATA SHEET

UR1087

635010 Adhesive, DUI Glue, 4 Oz. Can

MANUFACTURER'S NAME:
Clifton Adhesive, Inc.
Burgess Place
Wayne, N.J. 07470

INFORMATION AND EMERGENCY
PHONE NUMBER: 973-694-0845

IN CASE OF SPILL OR LEAK INVOLVING
THIS MATERIAL-CALL CHEMTREC 24
HOURS A DAY AT 800-424-9300

DATE OF PREPARATION: 06-27-07

DOT NAME & NO.:

ADHESIVES, UN1133

SECTION I - PRODUCT IDENTIFICATION

PRODUCT NAME: UR1087

HMIS RATINGS: H F R PP
2 3 0 B

SECTION II - HAZARDOUS INGREDIENTS

THE FOLLOWING * ARE REPORTABLE UNDER SARA TITLE III-SECTION 313:

TOP FIVE AND/OR

HAZARDOUS INGREDIENTS:

CAS NUMBER

ACGIH
TLV

OSHA PEL

Toluene 29-34%

*108-88-3

20 ppm

200 ppm

Methyl Ethyl Ketone 26-31%

78-93-3

200 ppm(BEI)

200 ppm

Acetone 26-31%

67-64-1

500ppm(BEI)

1000 ppm

TSR # 1397250002-5011P

TSR # 1397250002-5002P

TSR # 1397250002-5100P

Above exposure limits are for air levels only. When skin contact occurs, overexposure may result though air levels are less than limits listed above.

SECTION III - PHYSICAL DATA

BOILING Point: 123 - 143 Deg F.

VAPOR DENSITY: 2.37 - 2.77

VAPOR PRESSURE (mm Hg @ TEMP): 91.9 - 98 @ 20 deg C/68 deg F

SPECIFIC GRAVITY: 0.84 - 0.88

WEIGHT/GAL: 6.96 - 7.36

APPEARANCE AND ODOR: Neutral Liquid. Characteristic Solvent Odor.

VOLATILE ORGANIC COMPOUND #/GAL.: 6.08 - 6.38

VOLATILE ORGANIC COMPOUND KG/LITER: 0.73 - 0.77

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: -4 Deg. F.

METHOD USED: TCC

FLAMMABLE LIMITS IN AIR % LEL 1.2

UEL 13.0

AUTO IGNITION TEMPERATURE: 759 Deg. F.

EXTINGUISH MEDIA: Co 2, foam, dry chemical

SPECIAL FIRE FIGHTING PROCEDURE:

MATERIAL SAFETY DATA SHEET

UR1087

NIOSH/MSHA -approved self-contained breathing apparatus should be worn. Use water spray to cool fire exposed structures and disperse vapor cloud if fire is not present.

UNUSUAL FIRE AND EXPLOSION HAZARD:

Vapor is heavier than air and may travel considerable distance to source of ignition and flashback.

=====
SECTION V - REACTIVITY DATA
=====

STABILITY: Stable

INCOMPATIBILITY (MATERIALS TO AVOID);

N/A

CONDITIONS TO AVOID:

Avoid heat, open flames, sparks, hot surfaces, and oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS:

Oxides of carbon, nitrogen.

HAZARDOUS POLYMERIZATION: Will not occur.

=====
SECTION VI - HEALTH HAZARD DATA
=====

EFFECTS OF OVEREXPOSURE:

ACUTE: Nausea and/or narcosis.

CHRONIC: May damage nervous system. Numbness and tingling of arms and legs. Minor embryotoxic/fetotoxic effects have been observed in laboratory rats exposed to MEK by inhalation at levels greater than 1000 ppm (5 times the OSHA-PEL) for most of the gestation period.

TARGET ORGANS: Toluene may cause kidney abnormalities. MEK, based on animal data, may cause liver abnormalities, kidney, lung & brain damage. Teratogen. Acetone may cause liver or kidney damage.

SIGNS AND SYMPTOMS OF EXPOSURE:

Irritation to eyes and mucous membranes. Can also cause skin dryness. Liquid ingestion may result in vomiting. Can cause severe eye burns.

CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE:

Respiratory ailments.

CARCINOGENICITY No

WARNING: This product contains a chemical known to the State of California to cause cancer, birth defects and/or reproductive harm.

PRIMARY ROUTE(S) OF ENTRY: Inhalation, Eyes, Skin, Ingestion.

EMERGENCY AND FIRST AID PROCEDURES:

Utilize the suggested methods below. In emergency situations notify a physician immediately.

SKIN: Wash with soap and water. Get medical attention.

EYES: Flush eyes abundently with clean water and refer to physician.

INGESTION: DO NOT induce vomiting. Refer to physician.

EXCESSIVE INHALATION: Remove patient to fresh air or give oxygen. Use CPR if patient is not breathing. Refer to physician.

SECTION VII - SPECIAL PRECAUTIONS

HANDLING & STORAGE:

Store in approved solvent storage area. Keep tightly closed. Keep away from heat open flames, sparks, hot surfaces and oxidizing agents.

OTHER PRECAUTIONS: N/A

SECTION VIII - SPILL OR LEAK PROCEDURES

FOR SPILLS OR RELEASED MATERIAL:

Absorb spill in sand, earth, vermiculite, or other absorbent material. Shovel absorbed material into steel container and cover.

WASTE DISPOSAL METHOD:

Dispose of in accordance with federal, state, and local chemical and solvent waste disposal regulations.

SECTION IX - SAFE HANDLING AND USE INFORMATION

RESPIRATORY PROTECTION:

Use NIOSH-approved atmosphere supplying or air purifying respirator for organic vapors as required to maintain exposure levels below recommended limits.

VENTILATION: As specified.

LOCAL EXHAUST: Remove vapors during processing.

MECHANICAL EXHAUST: Explosion-proof equipment.

SPECIAL: Reduce vapor concentrations below specified limits.

PROTECTIVE GLOVES: PVA gloves

EYE PROTECTION: Safety glasses

OTHER PROTECTIVE EQUIPMENT:

Protective clothing as required to prevent skin contact.

HYGIENIC PRACTICES:

Keep area clean. Clean up spills immediately. Practice good personal hygiene.

DISCLAIMER LIABILITY: Since conditions or methods of use are beyond our control - we do not assume any responsibility and expressly disclaim any liability for any use of this product. The information contained in this MSDS is believed to be true and accurate but all statements or suggestions are made without warranty - express or implied regarding the accuracy of the information - the hazards connected with the use of the product or the results to be obtained from the use thereof. Compliance with all federal state and local laws and regulations remains the responsibility of the user.

USER'S RESPONSIBILITY: This MSDS cannot cover all possible situations which the user may experience during processing. You should examine each aspect of your operation and determine if additional precautions should be taken. All health and safety information contained in this MSDS should be provided to your employees or customers. It is your responsibility to use this information to develop appropriate work practice guidelines and employee training programs for your operation.